

RECEIVED
CENTRAL FAX CENTER

002/005

OCT 24 2007

60,130-1747; 03MRA0022

IN THE CLAIMS

1. (Currently Amended) A reinforced structural member comprising:
a hollow axle defining a cavity;
a bag disposed within said cavity defining a space;
a material disposed within said bag filling said space; and
a suspension component secured to said hollow axle proximate to said material, said hollow axle ~~includes including~~ a hole with a cap having a locating feature disposed in said hole, said locating feature positioning said suspension component.
2. (Currently Amended) The reinforced structural member assembly according to claim 1, wherein said ~~axle~~ ~~includes a hole~~ and said bag includes a compressed size equal to or smaller than said hole ~~facilitating to facilitate~~ insertion of said bag into said cavity.
3. (Currently Amended) The reinforced structural member assembly according to claim 2, wherein a said cap is installed in said hole ~~enclosing to enclose~~ said cavity.
4. (Currently Amended) The reinforced structural member assembly according to claim 2, wherein said bag includes an end having an opening facilitating insertion of said material into said bag.
5. (Currently Amended) The reinforced structural member assembly according to claim 4, wherein said end is disposed within said cavity.
6. (Currently Amended) The reinforced structural member assembly according to claim 1, wherein said material is a structural foam.
7. (Currently Amended) The reinforced structural member assembly according to claim 6, wherein said structural foam is a two-part epoxy.

60,130-1747; 03MRA0022

8.-17. (Cancelled)